SRCT / SRVT

150 PSI / 100 PSI Sanitary 316L Stainless Steel Cartridge Vessels

PRODUCT HIGHLIGHTS

SRCT SINGLE CARTRIDGE

- Maximum Operating Pressure: 150 psi (67°F)
- Electropolished finish ensures optimal cleanability in critical areas
- Stainless steel legs
- Sterilization using in-line steam, autoclave or hot water
- Fitted for code 7 filter cartridge

SRCT MULTI-CARTRIDGE

- Maximum Differential Pressure: 25 PSID
- Filter Cartridge Life: 0-25 PSID
- Electropolished finish ensures optimal cleanability in critical areas
- Stainless steel legs
- Sterilization using in-line steam, autoclave or hot water
- Fitted for code 7 and code 6 filter cartridges

SRVT SINGLE & MULTI-CARTRIDGE

- Maximum Operating Pressure: 100 psi (200°F)
- 316 Stainless steel
- Removable cartridge plates for cleaning
- Bleeder valve vents and drains
- Silicone Gaskets



SRCT Single Cartridge

PRODUCT DESCRIPTION

The SRCT and SRVT Sanitary Cartridge Vessels offer the aesthetics and operational durability of stainless steel at affordable prices. The SRCT's innovative design ensures optimal cleanability in critical areas and can accomodate either 10", 20" or 30" cartridges in a single cartridge housing and 20", 30" or 40" filter cartridges in a multi-cartridge vessel.

SRCT filters are designed specifically for liquid filtration in the food and beverage industry, offering microbiological safety, corrosion resistance and durability.

SRVT filters offer the same innovative design with a 100 PSI maximum operating pressure at 200°F.

CONSTRUCTION MATERIAL
316L Stainless Steel

FINISH
Electropolished SRCT

STERILIZATION
In-line steam, autoclave, or hot water

END CAP OPTIONS
C6: Flat/226, C7: Fin/226

INLET/OUTLET

SRCT
1TC: 1" Tri-Clover (1-cartridge housing only)
2TC: 2" Tri-Clove
3TC: 2" Tri-Clover (not available with 1-cartridge housing)

SRVT
1TC: 1" Tri-Clover (1-cartridge housing only)
1.5TC: 1.5" Tri-Clover (3,5,7-cartridge housing only)
2TC: 2" Tri-Clover (12-cartridge housing only)

MAXIMUM OPERATING PRESSURE

SRCT
145 psi (67°F)

SRVT
100 psi (200°F)

MAXIMUM DIFFERENTIAL PRESSURE

SRCT MULTIPLE
25 PSID



SRCVT
Multi- cartridge

CARTRIDGE COUNT

SRCT
1, 3, 5, 8, 12, 18, 24, 30 round cartridges

SRVT
1, 3, 5, 7, 12 round cartridges

ELEMENT LENGTH

SRCT
10", 20", 30", 40" (40" multi-cartridge only)

SRVT
10" (1-cartridge housing only), 20" (1-cartridge housing only), 30"

SPECIFICATIONS

SCAN FOR MORE INFO

We can build your vessel to suit your specifications.
Call one of our customer service representatives for pricing and availability.

ORDER OPTIONS

VESSEL	SRCT CARTRIDGE COUNT	SRVT CARTRIDGE COUNT	CARTRIDGE LENGTH	INLET/OUTLET	MATERIAL	END CAPS/O RING
SRCT Strainrite Sanitary Cartridge Vessel **SRVT** Strainrite Sanitary Cartridge Vessel – 100 psi	**1RND =** 1-round cartridge **3RND =** 3-round cartridges **5RND =** 5-round cartridges **8RND =** 8-round cartridges **12RND =** 12-round cartridges **18RND =** 18-round cartridges **24RND =** 24-round cartridges **30RND =** 30-round cartridges	**1RND =** 1-round cartridge **3RND =** 3-round cartridges **5RND =** 5-round cartridges **7RND =** 7-round cartridges **12RND =** 12-round cartridges	**SRCT** *10" 20" 30" **40" * 1-cartridge house only ** Not available with 1-cartridge **SRVT** *10" *20" 30"	**SRCT** **1TC** 1" Tri-Clover* **2TC** 2" Tri-Clover **3TC** 3" Tri-Clover **SRVT** **1TC** 1.5" Tri-Clover* **1.5TC** 1.5" Tri-Clover** **2TC** 2" Tri-Clover*** * 1-cartridge house only ** 3,5,7-cartridge house only *** 12-cartridge house only	**C** 316 Stainless Steel	**SRCT** **C6** Flat/226 **C7** Fin/226 **SRVT** **C7** Fin/226

SRCT	1RND	10	1	C	C6	
Series	Cartridge Count	Cartridge Length	Inlet/Outlet	Material	END CAP	SRCT1RND201CC6

THE STRAINRITE Companies | World Class Filtration