SRMS
Manifold Filtration Systems

PRODUCT HIGHLIGHTS

SRMS STANDARD

- -in volume displacer in cover (SRHD)
- 150 psi design, available to 300 psi
- Inlet/outlet orientation: Side-in/Bottom-out (standard)
- Easily cleaned
- Low pressure drop
- Stainless Steel wire mesh basket
- Positive cover seal
- ASME Code stamp available on all SRHD-style vessels

PRODUCT DESCRIPTION

Strainrite's SRMS Manifold Filtration Systems consist of two or more filter vessels piped in series or parallel. Strainrite offers countless configurations and flow designs depending on the user's specific needs. The standard design is to configure the vessels in parallel with isolation valves on each vessel.

A four-vessel system can also be configured in a box design, which allows for graduated filtration and continuous flow. Given the modular nature of manifold systems, throughput capability can be easily expanded or contracted as needed, and the footprint is adaptable to available space.

Contact our engineering personnel to configure the ideal system for your application.



SRMS

SRMS 4 Vessel



SRMS 3 Vessel



SPECIFICATIONS

SCAN FOR MORE INFO

CUSTOM SRMS



We can build your vessel to suit your specifications. Call one of our customer service representatives for pricing and availability.

ORDER OPTIONS

VESSEL	VALVE OPTIONS	VESSEL COUNT	BRANCH SIZE	MATERIAL	HEADER	VESSEL TYPE	OPTIONS
SRMS Manifold System	**N** No Valves **V** Valves	2 3 4 5 6 8 10	**2** 2″ pipe **3** 3″ pipe	**A** Carbon Steel **B** 304 Stainless Steel **C** 316 Stainless Steel	**2H** 2″ header **3H** 3″ header **4H** 4″ header **6H** 6″ header	**SRHD** **SRID**	**EP** Electro Polish Finish **MLB** Mesh-Lined Basket **UM** Code Stamped **U** 3rd Party ASME Code Inspected **SSB** Swing Bolts/Eye Nut Stainless Steel **DPG** Differential Manifold Pressure Gauge Ports

SRMS	2	4	2	A	2H	SRID	U	SRMSN42A2HSRIDU
SERIES	VALVE	VESSEL COUNT	BRANCH SIZE	MATERIAL	HEADER	VESSEL	OPTIONS	

THE STRAINRITE Companies | World Class Filtration